



INTRODUCTION

GH018-Z

GH018-Z type yarn oil special winder, used in chemical fiber, filament, low stretch yarn, polypropylene, nylon, silicone oil/ liquid wax and winding into a cone or a cylinder, for the next process, good forming, without the phenomenon of edge collapse. GH018-Z type to alleviate the labor intensity of the process, adaptation high speed production. (For the major manufacturers: lace factory, knitting factory, circular knitting machine, hosiery machine etc..)

Note:

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Technical characteristics	Technical parameters
Bobbin spec	6" (170mm)
Layout	Double sides, per machine has (12-96)spindles
Power supply	Three-phase 380V 50/60HZ
Transmission	Every spindle is driven by a AC motor individually
Power consumption	0.09kW/spindle
Take-up package	Cylindrical (D" : cone, 4" 20" 31" 51" 51" 51" 51" cone)
Package diameter	Max. 200 and 290mm
Yarn speed	800-1000m/min
Anti overlapping electronic device	Control by the inverter
Length counting device	Programmable controller (PLC) centralized control / display meter
Tension device	Every spindle has a self-cleaning yarn tension and wasser adjusting device
Slub catcher	Every spindle has a mechanical slub catcher
Yarn break control device	The spindle will stop when the yarn breaks by a yarn break control device
Speed regulation	Frequency control
Soft package edge traverse device	Mechanical/suitable for loose type
Electronic yarn cleaner	Ordered separately
Splicer	Ordered separately
Lighting system(lamp)	Ordered separately
Dimensions	11700(length)×1050(width)×1650(height)mm