

Nesting	MSK2513D100	MSK2513D200	MSK2513D300	MSK2513D200LT	MKSK2513D300LT
Picture					
Working travel	2440*1250*160	2440*1250*160	2440*1250*160	2440*1250*160	2440*1250*160
Max. working size	2440*1250*60	2440*1250*60	2440*1250*60	2440*1250*60	2440*1250*60
Spindle power and speed	6.0kw/24000rpmx1	6.0kw/24000rpmx1 +4.5kw/18000rpmx1	6.0kw/24000rpmx1 +4.5kw/18000rpmx2	6.0kw/24000rpmx1 +4.5kw/18000rpmx1	6.0kw/24000rpmx1 +4.5kw/18000rpmx2
X speed	0-50m/min	0-50m/min	0-50m/min	0-50m/min	0-50m/min
Y speed	0-50m/min	0-50m/min	0-50m/min	0-50m/min	0-50m/min
Z speed	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min
X motor power	0.75kw	0.75kw	0.75kw	0.75kw	0.75kw
Y motor power	2*0.75kw	2*0.75kw	2*0.75kw	2*0.75kw	2*0.75kw
Z motor	0.75kw	0.75kw	0.75kw0.75kw	0.75kw	0.75kw
Drilling box type	-	-	-	Vertical 5+4	-
Labeling /load and unload	-/-	-/-	-/-	-/yes	-/yes
Tools	-	-	-	-	-
Servo/control system	Chinese/N C studio	Chinese/N C studio	Chinese/N C studio	Chinese/N C studio	Chinese/N C studio

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!