



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

PT. Valtekindo Global Intertek

LAMINATING PRESS

贴面压机系列

160吨热压机
160T hot press

技术参数 Technical parameter

型号 Model	BY214×8/16(3)H1RC	BY214×9/16(3)H1RC	BY214×10/16(3)H1RC	BY214×12/16(3)H1RC
公称总压力 Total pressure	1600KN	1600KN	1600KN	1600KN
工作层数 Working layer	3	3	3	3
有效工作幅面最大压强 Unit pressure	5kgf/cm ²	4kgf/cm ²	4kgf/cm ²	3.4kgf/cm ² ①
热压板数量及规格 Platen No&size	4-2500×1300×42mm	4-3000×1300×42mm	4-3200×1300×42mm	4-3600×1300×42mm
热压板间距 Opening	120mm	120mm	120mm	120mm
油缸数量及直径 Cylinder No&diameter	10-φ85mm	10-φ85mm	10-φ85mm	10-φ85mm
加热方式及介质 Heating way	电热介质循环 Electric heated with conduction oil	电热介质循环 Electric heated with conduction oil	电热介质循环 Electric heated with conduction oil	电热介质循环 Electric heated with conduction oil
压板开启方式 Hot platen open way	电动 Automatically	电动 Automatically	电动 Automatically	电动 Automatically
装机功率 Installation power	52.75KW	52.75KW	77.5KW	77.5KW
闭合速度 Closing speed	24mm/s	24mm/s	24mm/s	24mm/s

型号 Model	BY215×9/16(3)H1RC	BY215×10/16(3)H1RC	BY215×12/16(3)H1RC	BY214×8/30(3)H1RC
公称总压力 Total pressure	1600KN	1600KN	1600KN	3000KN
工作层数 Working layer	3	3	3	3
有效工作幅面最大压强 Unit pressure	3.6kgf/cm ²	3.3kgf/cm ²	3.0kgf/cm ²	8.1kgf/cm ²
热压板数量及规格 Platen No&size	4-3000×1500×42mm	4-3200×1500×42mm	4-3600×1500×42mm	4-2700×1370×42mm
热压板间距 Opening	120mm	120mm	120mm	100mm
油缸数量及直径 Cylinder No&diameter	10-φ85mm	12-φ85mm	12-φ85mm	8-φ150mm
加热方式及介质 Heating way	电热介质循环 Electric heated with conduction oil	电热介质循环 Electric heated with conduction oil	电热介质循环 Electric heated with conduction oil	电热介质循环 Electric heated with conduction oil
压板开启方式 Hot platen open way	电动 Automatically	电动 Automatically	电动 Automatically	电动 Automatically
装机功率 Installation power	77.5KW	77.5KW	77.5KW	53.5KW
闭合速度 Closing speed	24mm/s	20mm/s	20mm/s	17mm/s

产品不断改进，当外形与参数变更时，均以实样为准，恕不另行通知。
Products improving with design and parameter changes without prior notice.

CAS-1