

CNC DEVICE PARAMETER LIST

NESTING	MSK2513E	MSK2513E200	MSK2513E300	MSA2513A100	MSK2513A
Picture					
Working travel	2440&1250*200	2440*1250*200	2440*1250*200	2440*1250*200	2440*1250*200
Max. working size	2440*1250*180	2440*1250*60	2440*1250*60	2440*1250*60	2440*1250*60
Spindle power and speed	9.5kw/24000rpm x 1	6.0kw/24000rpm x 1 +4.5kw/18000rpm x 1	6.0kw/24000rpm x 1 +4.5kw/18000rpm x 1	9.5kw/24000rpm x 1	9.5kw/24000rpm x 1
X speed	0-60m/min	0-60m/min	0-60m/min	0-80m/min	0-80m/min
Y speed	0-60m/min	0-60m/min	0-60m/min	0-80m/min	0-80m/min
Z speed	0-30m/min	0-30m/min	0-30m/min	0-30m/min	0-30m/min
X motor power	0.85kw	1kw	1kw	0.85kw	1.3kw
Y motor power	2*0.85kw	2*1kw	2*1kw	2*0.85kw	2*1.3kw
Z motor power	0.85kw	1kw	1kw	0.85kw	1.3kw
Drilling box type	-	-	5+4	5+4	5+4
Labeling/Load and Unload	-/-	yes/yes	yes/yes	yes/yes	yes/yes
Tools	8x2	-	-	8 (10/12 optional)	8 (10/12 optional)
Servo/control system	YASKAWA/SYNTEC	DELTA/SYNTEC	DELTA/SYNTEC	YASKAWA/SYNTEC	YASKAWA/SYNTEC

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!