

Simpler operation. Less maintenance. Superior print quality. The all-new Videojet 1210 continuous ink jet printer is engineered to keep your line up and running longer. It's designed for customers who print six hours to eight hours per day, five days per week — providing up to 18 months of production before required preventive maintenance.

Advanced capabilities

- Up to 3 lines of code with speeds up to 533 ft./min. (162 m/min.)
- Standard USB with logo and memory back up features

Simple to maintain

- 6,000-hour core life
- No mess, no waste, no mistake fluid cartridge delivery system

Superior environmental protection

- IP55 wash-down protection standard

Font Matrix Configuration

Single-line: 5x5, 5x7, 7x9, 11x16, 17x24

Twin-line: 5x5, 5x7, 7x9

Tri-line: 5x5, 5x7

Nominal Character Height

Selectable from 0.079" (2 mm) to 0.279" (8.5 mm), depending on font

Character Sets

American, Arabic, Bulgarian, Chinese, East European, European, Greek, Hebrew, Hungarian, Italian, Japanese, Japanese/Kanji, Japanese/ Katakana, Korean, Russian, Simplified Chinese, Scandinavian, Thai, Traditional Chinese, Turkish, Vietnamese

Languages and Interface Options

English, Arabic, Bulgarian, Czech, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Thai, Traditional Chinese, Turkish and Vietnamese

Console Dimensions

Stainless steel

21.3" (541 mm) high

13.6" (345 mm) wide

11.2" (285 mm) deep

Temperature/Humidity Range

41°F to 113°F (5°C to 45°C)

0% to 90% RH non-condensing

Electrical Requirements

Nominal supply power 100-120 / 200-240 VAC at 50/60 Hz. 120 W

Approximate Weight

Unpacked and dry: 39.68 lbs. (18 kg)

Main parameter:

- 1) Modal : Lead jet S-320 (made in China)
- 2) Height of Character : 100 type spout (20mm)
- 3) Character Types : ASCII code
- 4) Spraying Speed : 0.5 meter/minutes~60meter/minutes (Max capacity for bottles: 10000 bottles per hour)
- 5) Interface : RS-232C
- 6) Memory Info : 80 documents
- 7) Software Function : the character is adjustable, the printing can be delayed, the width of the character, the direction of the printing, the reversion of the character, enlargement of the character, cleanout automatically .etc.
- 8) Electrical Voltage : 220V. 50/60 Hz
- 9) Operating environment : 38F~122F
- 10) Printing Ink : Diversified spraying ink (water craft, oil craft)
- 11) Printing Material : Osmosis and non-osmosis
- 12) Spraying Distance : 5 ~30mm

Automatic code printer Lead jet S-320



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!