



Basic parameters	model	KGT-4318A
	type]	Flatbed printer
	ink system	continue providing ink 150/M
	print DPI	2880*1440 DPI
	print speed	A2,about 5 minutes
Specification parameters	print way	no -contact inkjet printing(Micro Piezo printing technology)
	print direction	automatic single/bi-directional printing
	Nozzle configuration	1440 nozzles(180 nozzles*8 cartridges)
	minimum ink droplet size	3.5 pico-liter
Ink deploys	inking system	continuous refill system
	colour deploys	Y LM LC M C LLK LK MK PK PK MK ,PKand MKswitch automatically
Printing specification	maximum print area	431mm×750mm(can be designed according to customer)
	the height of print up and down	1mm-150mm
	print shower nozzle distance	1mm-5mm
Nontrol systems	jacking system	stepper motor+screw with simultaneous
	feeding system	stepper motor with timing bell 2GT Italy
	altitude checks	IC entire automatic monitoring prints altitude
	control mode	intelligent Taiwan touch screen
	Nozzle protection	infrared detection of automatic adjustment
Date transmission	language	intelligent touch-screen arbitrary switching in foreign languages
	interface deploy	USB 2.0(high speed)/IEEE 1394
	input buffer	128MB
Equipment Size	Transmission speed	64MBPS
	External form dimension	1150mm×890mm×605mm
	Carton dimension	1230mm×940mm×860mm
	Equipment net weight	90KG
	Equipment gross weight	123KG

KGT-4318A

Technical Parameter

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!