

4
Colours**Features :**

- 1. Machine Type :** Central impression type, film supported by the big drum, never leaving between colors, so register better.
- 2. Machine Structure :** Parts are commonized for availability, low-wear design.
- 3. Dryer:** Hot wind dryer, automatic temperature controller for printing material dry safety, provided by the separated heater box.
- 4. Doctor Blade :** Chamber doctor blade for high speed printing and quality printing.
- 5. Transmission :** High performance vector motor, buttons are placed in multiple places for machine start, up speed, down speed, stop, which makes operators more convenience. After machine start, it reach the preset speed automatically.
- 6. Rewinder Driving :** High performance ac motor, low friction cylinder for stable web tension.
- 7. Color Registration :** Electric motor type, Push buttons by up, down, left and right only.

Main Parameter

Machine Model	QTH-CI 4600	QTH-CI 4800	QTH-CI 41000	QTH-CI 41200
Max. Material Width	600 mm	800 mm	1000 mm	1200 mm
Max. Printing Width	550 mm	750 mm	950 mm	1150 mm
Suitable for Material	PAPER : 15~300 g/m ² , NONWOVEN : 15~120 G, PVC : 10~120 μm, OPP : 10~100 μm, BOPP : 10~100 μm, PE : 15~150 μm, NY : 10~120 μm, PET : 10~100 μm, CPP : 10~100 μm			
Colours	4 Colours			
Printing Repeat Length	380 – 1000 mm			
Central Drum Dia.	800 mm			
Machine Speed	200 m/min			
Printing Speed	150 – 180 m/min (depends on the material)			
Printing Precision	±0.1 mm			
Plate Thickness	1.7 mm (if different thickness, please note us)			

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!