



1. Unroll with tension to produce high and low level raw paper.
2. Adopting screw turning knife to cut, knife-blade is strong enough to operate fast without noise and shaking.
3. Glue equally
4. Electric controlled counter to ensure the weight of product.
5. The equipment can be have single color printing or two color printing according to customers' requirement.

Note :
Due to keeping innovation,
the specification and Machine
pictures or color are subject to
alteration without notice!

主要技术参数 Main Technical Parameters							
料型型号 Type	1092D	1576D	2000D	2200D	2400D	2600D	2800D
原煤容量 Width of coal container	1200	1750	1950	2150	2350	2550	2750
活系数 Live coefficient	物料堆积系数 COEF. TOPOGRAPHY FOR COAL IN CONTAINER						
活系数取值 Live rate of heaped product	0.90~0.95						
物料堆积 Live rate of coal	物料堆积系数 TOPOGRAPHY FOR COAL IN CONTAINER						
物料堆积系数 Live rate of coal	COEF. TOPOGRAPHY FOR COAL IN CONTAINER						
料斗容积 Pitchfork container	2.2150 (斗容量) 其它规格请洽商 2.2150 (pitchfork capacity) others please contact						
卸车速度 Unloading speed	1.00~1.50 (斗容量) 1.00~1.50 (pitchfork capacity)						
上料解套系统 Unloading system	上料解套系统 Unloading system with upper unloading roller, upper roller						
溢流器 Flow material divider	2个 2 pieces						
电动机 Electric motor	电动机功率 Electric motor power (kw)						
功率 Power	5~10 KW						
电动机式 (kW/44) Motor (kW/44)	电动机功率 Electric motor power (kW/44)						
速度 Speed	3~40T						
重量 Weight	重量 Weight						
电动机 Electric motor	电动机功率 Electric motor power (kW/44)						
电动机 Electric motor	电动机功率 Electric motor power (kW/44)						

