

Full automatic Three-color soles injection moulding machine

Use and character:

1. PLC program control of industrial man-mach interface\Display of tactile screen\Quick speed\Precise measurement\Full automatic operation
2. The working statement is monitored all the while, for person to adjust the parameters easily if necessary.
3. It is applied to produce one-color\two-color\three-color soles.
4. The machine has economy design, it takes up only small space, saving energy, asking for fewer operators.

Suitable material: PVC, TPR

Produce: single, double and three color soles

KR38024

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!



项目Items	单位Units	KR38024
加工原料 Material	kind	TPR/PVC
模位数 Mould stations	stations	24
注射容量 Injection capacity (Max.)	g	800/650X2
注射精度 Injection measuring accuracy	g	±0.5
额定注射压力 Injection pressure	kg/cm2	760/560X2
螺杆直径 Diameter of screw	mm	75/65X2
螺杆转速 Rotate speed of the screw	r/min	1-160
合模力 Clamping pressure	kn	3X700
模板尺寸 Mold size	mm	500X300X230
温控段数 Temperature control	point	4X3
油泵压力 Hydraulic pressure	Mpa	21X3
开模行程 Opening stroke of mould	mm	300
油箱容量 Oil tank capacity	kg	450
加工产量 Output	x/h	1-200
加热功率 Power of heating plate	kw	9X3
电机功率 Power of motor	kw	18.5X3
总机功率 Total power	kw	82.5
机器尺寸 Dimension(LxWxH)	M	10X7.8X2.5
机器重量 Machine weight	T	24.8