

Full automatic multi-functional PVC blowing injection moulding machine

Use and character:

1. PLC program control of industrial man-machine interface, Display of tactile screen, Full automatic operation
2. Full state control, intuitively set of parameters.
3. Equipped with air blow system, the produce is light-weight & soft & micro-foraming & highly-felxibility & bright surface & no painting & environmental.
4. Save energy.
5. Produce all kinds of slippers, Single & Double & three color soles, three color upper



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

Suitable material: PVC、TPR

Produce: various kinds of pvc soles , silpper , sandler , strap , etc.

KR38024Q-X3



项目Items	单位Units	KR38024Q-X3
加工原料Material	Kind	TPR、PVC
模位数Mould stations	stations	20、24、30
注射容量Injection capacity(Max.)	g	700/250X2
注射精度Injection measuring accuracy	g	±0.5
额定注射压力Injection pressure	kg/cm ²	760/900X2
主机螺杆直径Diameter of screw	mm	65/45X2
螺杆转速Rotate speed of the screw	r/min	1-160/180X2
合模力Clamping pressure	kn	700X2
模板尺寸Mold size	mm	500X350X280 500X700X280
加热功率Power of heating plate	kw	12
电机功率Power of motor	kw	18.5+11
油泵压力Oil pump pressure	Mpa	21X2
总装机容量Power of machine	kw	41.5
机器尺寸Dimension(LxWxH)	M	8.5X3.8X2.5
机器重量Machine weight	T	10.7