



Full automatic One-color strap injection moulding machine



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

项目Items	单位Units	KR8020	KR8020	KR8020
加工原料Material	kind	TPR/PVC	TPR/PVC	TPR/PVC
模位数Mould stations	stations	20	24	30
注射容量Injection capacity (Max.)	g	800	800	800
注射精度Injection measuring accuracy	g	±0.5	±0.5	±0.5
额定注射压力Injection pressure	kg/cm ²	760	760	760
螺杆直径Diameter of screw	mm	75	75	75
螺杆转速Rotate speed of the screw	r/min	1-160	1-160	1-160
合模力Clamping pressure	kn	700	700	700
容模空间Size of mold holder	mm	500X250X230	500X250X230	500X250X230
温控段数Temperature control	point	4X1	4X1	4X1
油泵压力Hydraulic pressure	Mpa	21X1	21X1	21X1
开模行程Opening stroke of mould	mm	300	300	300
油箱容量Oil tank capacity	kg	450	450	450
加工产量Output	x/h	1-220	1-230	1-250
加热功率Power of heating plate	kw	9X1	9X1	9X1
电机功率Power of motor	kw	18.5X1	18.5X1	18.5X1
总机功率Total power	kw	27.5	27.5	27.5
机器尺寸Dimension(LxWxH)	M	3.8X2.6X2.5	3.8X3X2.5	3.8X3.8X2.5
机器重量Machine weight	T	4.3	4.5	5.7

上述资料仅供参考，如因设计与制造上的需要变更规格、尺寸、则不另行通知！
Specifications are subject to change request without notice for improvement !