

# Full automatic Three-color soles injection moulding machine



**Note :**  
Due to keeping innovation,  
the specification and  
Machine pictures or color  
are subject to alteration  
without notice!

| 项目Items                           | 单位Units  | KR38024     |
|-----------------------------------|----------|-------------|
| 加工原料 Material                     | kind     | TPR/PVC     |
| 模位数 Mould stations                | stations | 24          |
| 注射容量 Injection capacity ( Max. )  | g        | 800/650X2   |
| 注射精度 Injection measuring accuracy | g        | ±0.5        |
| 额定注射压力 Injection pressure         | kg/cm2   | 760/560X2   |
| 螺杆直径 Diameter of screw            | mm       | 75/65X2     |
| 螺杆转速 Rotate speed of the screw    | r/min    | 1-160       |
| 合模力 Clamping pressure             | kn       | 3X700       |
| 模板尺寸 Mold size                    | mm       | 500X300X230 |
| 温控段数 Temperature control          | point    | 4X3         |
| 油泵压力 Hydraulic pressure           | Mpa      | 21X3        |
| 开模行程 Opening stroke of mould      | mm       | 300         |
| 油箱容量 Oil tank capacity            | kg       | 450         |
| 加工产量 Output                       | x/h      | 1-200       |
| 加热功率 Power of heating plate       | kw       | 9X3         |
| 电机功率 Power of motor               | kw       | 18.5X3      |
| 总机功率 Total power                  | kw       | 82.5        |
| 机器尺寸 Dimension(LxWxH)             | M        | 10X7.8X2.5  |
| 机器重量 Machine weight               | T        | 24.8        |

上述资料仅供参考，如因设计与制造上的需要变更规格、尺寸、则不另行通知！  
Specifications are subject to change request without notice for improvement !