



Full automatic PVC two color rain boots injection molding machine



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

项目Items	单位Units	KR2160012W
加工主机注射容量 Main machine injection capacity	g	1100
主机螺杆直径 Diameter of screw	mm	85
副机注射容量 Auxiliary machine injection capacity	g	850
副机螺杆直径 Diameter of auxiliary screw	mm	75
注射精度 Injection measuring accuracy	g	±0.5
主机额定注射压力 Injection pressure of main machine	kg/cm ²	560
副机额定注射压力 Injection pressure of auxiliary machine	kg/cm ²	760
螺杆转速 Rotate speed of the screw	r/min	0-160
合模力 Clamping pressure	TONS	150(主) 75(副)
压模力 Clamping pressure	TONS	20
容模空间 Mold size	mm	380x200x660
加热功率 Power of heating plate	kw	9x2
电机功率 Power of motor	kw	18.5(主) 15(副)
总装机容量 Total power	kw	55
加工原料 Material		PVC、TPR 塑性料
模位数 Mould stations	位	12
机器尺寸 Dimension(LxWxH)	m	6.5x6x3
机器重量 Machine weight	T	21

上述资料仅供参考，如因设计与制造上的需要变更规格、尺寸、则不另行通知！

Specifications are subject to change request without notice for improvement !

PT. Valtekindo Global Intertek

WINDY-1