

# skripsi mesinrajut sarungtangan model : BX203-7G

**Note :**

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

| Model           | BX203                                                                                                                                                                                                                                                                                                                                           |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size in needles | L2 : 52                                                                                                                                                                                                                                                                                                                                         |
|                 | L : 46                                                                                                                                                                                                                                                                                                                                          |
|                 | M : 42                                                                                                                                                                                                                                                                                                                                          |
|                 | S : 37                                                                                                                                                                                                                                                                                                                                          |
| Container load) | 40 sets/ 20'FT                                                                                                                                                                                                                                                                                                                                  |
|                 | 82 sets/ 40'HQ                                                                                                                                                                                                                                                                                                                                  |
| Power           | Single phase, 220V, 250W                                                                                                                                                                                                                                                                                                                        |
| Lubrication     | Manual lubrication                                                                                                                                                                                                                                                                                                                              |
| Dimension       | 1.230mm (L) x 650mm (W) x 1,700mm (H)                                                                                                                                                                                                                                                                                                           |
| Weight          | 250KG                                                                                                                                                                                                                                                                                                                                           |
| Options         | <ol style="list-style-type: none"> <li>1. X-yarn device</li> <li>2. Size changing device</li> <li>3. 3-finger palm/ D3 device</li> <li>4. Strong crotch device</li> <li>5. Two-color and three-color device</li> <li>6. Six-color knitter device</li> <li>7. Half-finger/mitten glove device</li> <li>8. Infrared safety area sensor</li> </ol> |

**Features:**

1. Sinker knitting system: with this system, it offers products that are superior in stretch and strength as well as featuring excellent conformity to the shape of hands.
2. Durable needle bed: it is formed by inserting special high-precision plates. Manufactured from special steel using state-of-the-art hardening technology, these plates provide extreme strength and durability for high-speed, high quality product manufacturing.
3. High-precision carriage: the carriage and cam systems are made of carefully selected steel and manufactured using a special computer-controlled hardening process, which increases its durability and anti-resistance.
4. User-friendly control panel: it focuses on ease of operation. Large LED displays communicate current knitting conditions at a glance. Touch-control numerical keys also offer convenient data input.

**Options:**

1. X-yarn device : it eliminates the necessity for using post-knit overlock sewing machines at the cuffs. The X-yarn device is therefore an effective way to cut manual labor costs and increase overall productivity.
2. Size changing system: with this device, two different sized gloves can be knitted. It helps realize greater versatility and more economical production planning.
3. 3-Finger palm device: with this option, the upper palm portion below the middle-three fingers is knitted separately from the rest of the palm. This provides independent movement and more comfortable and better fit.
4. Strong crotch device: with this device, it can produce gloves with higher friction resistance between the thumb and the forefinger.
5. 2-color and 3-color devices: with these devices, it can make magic gloves with 2 or 3 colors.
6. Infrared safety area sensor: The new area sensor features an invisible protective shield of infrared beams, which when broken stops the machine automatically. The area sensor reduces the likelihood of injury from moving parts, and allows maintenance and cleaning to be performed without removing and replacing safety covers.