

CNC LATHE MACHINE

Convincing arguments: quality, efficiency and price

- Range of gear wheel shift, variable frequency control and speed change is wide, torque in low-speed is big
- Whole stand, high rigidity, stable precision

Optional accessories:

- 8-step horizontal electric turret
- Hydraulic chuck with inside empty
- CNC rotaty turning tool
- GSK988T numeral control system
- Fanuc oi mate numeral control system
- CE standard



L560



L660

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Standard Equipment



Tail-stock



Coolan Tank

Model	L560CNCx1000/1500	L660 CNC x 1500/2000
Code No.	1356000/1356100	1366000/1366100
Swing over bed	φ560mm	φ660mm
Swing over cross slide	φ355mm	φ440mm
Admits between	1000mm/1450mm	1500mm
Spindle bore	φ80mm	φ105mm
Range of spindle speed	32-2000 rpm	15-1500 rpm
X-travel	250mm	370mm
Z-travel	1340mm	1460mm
Nos. of tool position	8	6 or 8
Max.section of tool	25x25mm	32x32mm
Main motor power	7.5KW	7.5KW
Packing size(LxWxH)	3400x1400x2240mm	3300x2300x2200mm
NW/GW	2350/2750kg	2100/3600kg