



Bench CNC Lathe stepper Only



Specification

WORKING AREA	Turning diameter over bed/over	200mm
	Travel across slide	150mm
	Center width	300mm
SPINDLE	Chuck diameter	150mm
	Spindle speed	50-3000rpm
	Spindle through-hole	20mm
	Spindle motor	MT3
	Spindle motor power	500W
FEED	X feed	150mm
	Z feed	30mm
	The max moving speed	3000mm/min
	The max feeding speed	300mm/min
TOOL REST	Tool position	4
	Tool dimension	8mm
TAILSTOCK	Tailstock type	MT2
	Tailstock sleeve diameter	17mm
ACCURACY	Positioning accuracy	0.01mm
	Repeatability accuracy	0.01mm
OTHERS	Power	220V or 110V
	Weight (NW/GW)	210/250kg
	Overall dimension	1000-750-1000mm
	Packing size	1200-950-1700mm



OPTIONAL ACCESSORIES



Bench CNC Lathe stepper Only



Specification

WORKING AREA	Turning diameter over bed/over	200mm
	Travel across slide	90mm
	Center width	280mm
SPINDLE	Chuck diameter	150mm
	Spindle speed	50-3000rpm
	Spindle through-hole	20mm
	Spindle motor	MT3
	Spindle motor power	500W
FEED	X feed	200mm
	Z feed	30mm
	The max moving speed	3000mm/min
	The max feeding speed	300mm/min
TOOL REST	Tool position	8
	Tool dimension 4 internal & external	40/50mm
TAILSTOCK	Tailstock type	MT2
	Tailstock sleeve diameter	12mm
ACCURACY	Positioning accuracy	0.01mm
	Repeatability accuracy	0.01mm
OTHERS	Power	220V or 110V
	Weight (NW/GW)	210/250kg
	Overall dimension	1075-685-1100mm
	Packing size	1280-980-1800mm



PT. Valtekindo Global Intertek

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

SG-4