

CNC LATHE MACHINE



Standard accessories:

- FANUC OI-TD/GSK/SIEMENS
- Coolant system
- Standard working lamp
- 4-step electric turret
- Heavy-type 4-jaw chuck (screw, wrench)
- Spindle taper Morse tape 6#
- Turret plate
- Steady rest
- Overlapping dual-sliding door semi-protective housing
- Automatic lubricating system
- Powerful fan
- Electric tail-stock
- Center sleeve

Optional accessories:

- Hydraulic tail-stock and hydraulic chuck
- 6-step electric turret
- 8-step electric turret
- Follow-rest

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

Model	SK61128	SK61148	SK61168	SK61198	SK61208
Code No.	1312200	1314200	1316200	1319200	1320200
Max swing over bed	Ø1280mm	Ø1480mm	Ø1680mm	Ø1980mm	Ø2080mm
Max swing over cross slide	Ø840mm	Ø1040mm	Ø1240mm	Ø1540mm	Ø1640mm
Spindle hole	Ø130mm	Ø130mm	Ø130mm	Ø130mm	Ø130mm
Bed width	1100mm	1100mm	1100mm	1100mm	1100mm
Diameter of tailstock sleeve	Ø260mm				
Spindle speeds(Number)	3.15-315r/min or 2.5-250(21)r/min or 2-200r/min 5-2015-6025-10065-250				
Main motor power	30KW				
Net weight	(SK61168×4000mm)22000kg				
Dimension	(SK61168×4000mm)7300×3000×2500mm				