



B、 (beam part)

(1) Model	whole beamer
(2) Frame	steel-welded
(3) weave-beam transmission	belt transmission
Motor	15kw
Convertor	ABB , 15kw
beam speed	0~100m/min
beam tension	0~6000N
speed error	$\leq \pm 1m$
(4)beam-tension control	steel-belt brake controlled pneumatically
(5)Power	pneumatic cyl.
(6)tension set style	adjusting valve、 gauge display
(7)weave-beam brake	steel-belt brake
(8)beam doff	pneumatic doffing
(9)safety equipment	safety rod
(10)operation board	TE switch
(11) Waxing device (depend on requirement, not standard)	usually three roll type
Speed control	synchronize with yarn speed
Speed set up	manual
Pump	stainless steel pump

C、 (reed frame)

(1)(frame)	(welded with swage)
(2)(reed)	(stainless steel reed)
(3)(division board)	(Al oxide ceramic)
(4)(moving control)	(cyl.)
(5)(grasp control)	(rotary cyl.)

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

D、 (creel)

(1) (style)	(rewind H type bobbin creel)
(2)(tension)	(flying ring tension device)
(3)(stop equipment)	(infrared)
(4)(spindles)	(640 spindles)
(5)(leaves)	8 layers
(6)(spindle distance)	250 × 250